

VSI-FAX 6.3 TECHNICAL SPECIFICATIONS

Unix Platforms

- **CPU:** RISC 500 MHz, Intel® Pentium® 2.60 GHz dual core or higher
- **Memory:** 2 GB RAM (4 GB recommended)
- **Hard disk space:** 200 MB permanent disk space plus 200 MB additional temporary space required during installation
- **Network interface card:** 100baseT or higher, configured with the latest drivers for your platform

Qualified and recommended platforms

- Sun Solaris SPARC® 9 (32-bit or 64-bit with SPARC v8/32-bit applications support)
- Sun Solaris Intel 10 (32-bit or 64-bit x86/32-bit applications support)
- IBM AIX 5.1, 6.1 or 7.2
- HP-UX 11i v1 (B.11.11)
- SCO Open Server™ 5.0.7 and 6.0
- SCO UnixWare® 7.1.3
- Red Hat® Enterprise versions 5 and 6 (32-bit x86, 64-bit x86_64), and 7 (64-bit x86_64)

Fax hardware

- On Red Hat platforms only: MultiTech® MT9234ZBA-USB-CDC-XR modem (for more than one modem, Esker recommends using a Belkin® F4U018-BLK USB Port Hub)

Outsourced fax

- Fax on Demand connector to send faxes through the Esker outsourced fax service
- Uses HTTPS Internet connection, no proxy server

Windows Platforms

Computer hardware

- **CPU:** Intel Pentium 2.60 GHz dual core or higher
- **Memory:** 2 GB RAM (4 GB recommended)
- **Hard disk space:** 200 MB permanent disk space plus 200 MB additional temporary space required during installation
- **Network interface card:** 100baseT or higher, configured with the latest drivers for your platform

Qualified and recommended platforms

- Windows® Server 2019 with Desktop Experience (Standard or Datacenter Edition)
- Windows® Server 2016 with Desktop Experience (Standard or Datacenter Edition)
- Windows Server 2012/2012 R2 (Standard Edition or Datacenter Edition)
- Windows Server 2008 R2 (Standard Edition, Enterprise Edition, or Datacenter Edition) with the Service Pack 1 and the latest Windows updates installed

Fax hardware

- Dialogic® Brooktrout® TR1034 series and TruFax series fax boards, or Dialogic Brooktrout SR140 Fax Software
- MultiTech MT9234ZBA-USB-CDC-XR modem (for more than one modem, Esker recommends using a Belkin F4U018-BLK USB Port Hub)

Outsourced fax

- Fax on Demand connector to send faxes through the Esker outsourced fax service
- Uses HTTPS Internet connection, no proxy server

VSI-FAX Server Administration

Computer hardware

- **CPU:** Intel Core™ i3 3.30 GHz dual core or higher
- **Memory:** 2 GB RAM
- **Hard disk space:** 25 MB
- **Network interface card:** 100baseT or higher, configured with the latest drivers for your platform

Qualified and recommended platforms

- All Windows qualified platforms for VSI-FAX Server
- Microsoft Windows 10
- Microsoft Windows 8, 8.1
- Microsoft Windows 7 SP1

LanFax Windows Client

Computer hardware

- **CPU:** Intel Core™ i3 3.30 GHz dual core or higher
- **Memory:** 2 GB RAM (4 GB recommended)
- **Hard disk space:** 100 MB
- **Network interface card:** 100baseT or higher, configured with the latest drivers for your platform

Qualified and recommended platforms

- Windows Server 2019 with Desktop Experience and with or without Desktop Services
- Windows Server 2016 with Desktop Experience and with or without Desktop Services
- Windows Server 2012/2012 R2 (Essentials Edition, Standard Edition, or Datacenter Edition) with the latest Windows updates installed, with or without Remote Desktop Services
- Windows Server 2008 R2 (Standard Edition, Enterprise Edition, or Datacenter Edition) with the Service Pack 1 and the latest Windows updates installed, with or without Remote Desktop Services
- Microsoft Windows 8, 8.1
- Microsoft Windows 7 SP1

CoverMaker

Qualified and recommended platforms

- Microsoft Windows 10
- Microsoft Windows 8
- Microsoft Windows 7 SP1

MailMerge Client

Computer hardware

- **CPU:** Intel Core™ i3 3.30 GHz dual core or higher
- **Memory:** 2 GB RAM (4 GB recommended)
- **Hard disk space:** 100 MB

Qualified and recommended platforms

- Microsoft Windows 10:
 - Office 2016
 - Office 2019
- Microsoft Windows 8, 8.1:
 - Office 2013
 - Office 2010
- Microsoft Windows 7 SP1:
 - Office 2010

©2019 Esker S.A. All rights reserved. Esker and the Esker logo are trademarks or registered trademarks of Esker S.A. in the U.S. and other countries. All other trademarks are the property of their respective owners.



Esker, Inc.
1850 Deming Way, Suite 150
Middleton, WI 53562
Tel: 800.368.5283 | **Fax:** 608.828.6001
Email: info@esker.com | **Web:** www.esker.com

Get Social

Blog: blog.esker.com